

# EEZ PRODUCTS

## SAFTEE CUT

*Universal Cutting Oil  
No Sulfur, No Chlorine*

For More Info, Visit..

[EEZProducts.com](http://EEZProducts.com)

*Foamy Cutting Fluid  
Tuf Tap 2-15-T  
Insted-A-Led*

*Micro Max  
Cool Aid  
Ultrafinish*

*Saftee Cut  
Thread Cut Cutting Oils*

*White Kut Soluble Oils  
Clean Wheel Coolants  
Cost Cut Synthetic Coolants*

*Saw Cut #683  
Delta #900 Coolants  
XP Rust Preventives*

*Saver Chain & Cable Fluid  
Way Oil  
Hydraulic Oil*

*Spindle Oil  
Compressor Oil  
Grease*

*Synthetic Gear Oil  
Synthetic Hydraulic Oil*

*Made In U.S.A.*

**Mullen Circle Brand, Inc.  
EEZ Products Division**

3514 West Touhy Ave  
Skokie, IL 60076  
847/676-1880

Fax: 847/676-3748

[Solutions@MullenOil.com](mailto:Solutions@MullenOil.com)



*Severe Machining Without Sulfur/Chlorine  
No Stink, No Rust*

**Saftee Cut** is a revolutionary cutting oil for applications of the greatest severity or requiring the finest finishes. This powerful product can be used on all ferrous and nonferrous metals.

### Applications

*Precision Grinding  
Deep Hole Drilling  
Gundrilling*

*Swiss Machining  
CNC Machining  
MQL Systems*

### Benefits

*Dramatically Better Tool Life  
Much Cooler Parts  
Reduced Smoke/Mist*

*Nonhazardous Waste Profile  
Multi-Metal Safe  
No Rust Or Corrosion*

*More ==>*

**...Providing Solutions To Industry Since 1912...**

# Mullen Circle Brand, Inc.

## EEZ PRODUCTS DIVISION

3514 W. Touhy Avenue  
Skokie, IL 60076

Phone 847/676-1880

Fax 847/676-3748

[Solutions@MullenOil.com](mailto:Solutions@MullenOil.com)

## EEZ PRODUCTS SAFTEE CUT

<b>Viscosity, SUS @ 100 F</b>	100
<b>Color</b>	Amber
<b>Odor</b>	Mild
<b>Flash Point, F</b>	390
<b>Pounds/Gallon</b>	7.1
<b>Sulfur</b>	—
<b>Chlorine</b>	—
<b>Fat</b>	X
<b>Phosphorous</b>	X
<b><u>Applications:</u></b>	
GundrillinG	X
Deep Hole Drilling	X
Precision Grinding	X
Swiss Machining	X
CNC Machining	X
Precision Threading	X

### Using Saftee Cut

**Saftee Cut** is a neat oil, intended to be used as supplied.

Certain other additive technologies will prevent **Saftee Cut** from working, so it cannot be added to other cutting oils and nothing should be added to it.

Due to this sensitivity issue, the tank needs to be drained, and ideally flushed. The results will make the results worthwhile.

*...Providing Solutions To Industry Since 1912...*

**Cutting Fluids \* Industrial Lubricants \* Greases \* Cleaners**

The Information Given Herein Is Believed To Be Reliable, But No Guarantee Is Made Nor Liability Assumed.