

MULLEN CIRCLE BRAND

STERLING H *PAO/ESTER Hydraulic Oil*

**Mullen
Circle Brand
Blended Products:**

*Cutting Oils
Circle Cut #729
Soluble Oils
Synthetic Coolants*

*Semi-Synthetic Coolants
Rust Preventives
Cleaners
Grease*

*Hydraulic Oil
Compressor Oil
Gear Oil
Way Oil*

*Spindle Oil
Machine Oil
Synthetic Oil*

Made In U.S.A.



Mullen Circle Brand, Inc.
3514 West Touhy Ave
Skokie, IL 60076
847/676-1880
Fax: 847/676-3748
Solutions@MullenOil.com



***100% Pure Synthetic for Max Life/Benefit
When You Need The Best***

Sterling H Oils are a family of PAO/Ester synthetic oils intended for use in hydraulic systems and compressors operating in severe environments. These oils exhibit low volatility and low pour points to ensure optimum performance over the entire temperature spectrum.

Sterling H Oils pass 10,000 hours in the turbine oil test (TOST), exhibiting exceptional thermal and oxidative stability. The high viscosity index reduces ambient temperature viscosity, thus enabling faster and more efficient air release.

Sterling H Oils are compatible with petroleum seals and petroleum oils, but mixtures of the two types of fluids will not yield all the benefits of using **Sterling H Oils** by themselves.

More ==>

...Providing Solutions To Industry Since 1912...



Mullen Circle Brand, Inc.

3514 W. Touhy Avenue
Skokie, IL 60076

Phone 847/676-1880

Fax 847/676-3748

Solutions@MullenOil.com

STERLING H SYNTHETIC HYDRAULIC OILS

| | H-32 | H-46 | H-68 | H-100 | H-150 | H-220 | H-320 | H-460 | H-680 |
|-----------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Viscosity, | | | | | | | | | |
| Cst 40 C | 32 | 46 | 68 | 100 | 150 | 220 | 320 | 460 | 680 |
| Cst 100 C | 5.9 | 8.3 | 11.5 | 15.0 | 22.0 | 30.0 | 40.0 | 53.0 | 76.0 |
| ISO Grade | 32 | 46 | 68 | 100 | 150 | 220 | 320 | 460 | 680 |
| Color | Clear | Clear | Clear | Clear | Clear | Clear | Clear | Clear | Clear |
| Flash Point, F | 460 | 460 | 460 | 460 | 460 | 460 | 460 | 460 | 460 |

H-1000 H-1500

| | | |
|-----------------------|-------|-------|
| Viscosity, | | |
| Cst 40 C | 1000 | 1500 |
| Cst 100 C | 102.0 | 138.0 |
| ISO Grade | 1000 | 1500 |
| Color | Clear | Clear |
| Flash Point, F | 460 | 460 |

...Providing Solutions To Industry Since 1912...

Cutting Fluids * Industrial Lubricants * Greases * Cleaners

The Information Given Herein Is Believed To Be Reliable, But No Guarantee Is Made Nor Liability Assumed.